



**DECLARATION OF PERFORMANCE No 0556**

1. Unique identification code of the product-type: **KERAKLIMA ECO**
2. Intended use/es: **General purpose mortar (GP), on external walls, ceilings and columns.**
3. Manufacturer: **Kerakoll Ibérica, S.A. – Ctra. Alcora Km 10,450 Castellón - España**
4. System/s of AVCP:  
**System 4**  
**System 3 for reaction to fire**
5. Harmonised standard: **EN 998-1:2016**  
Notified body/ies: **Istituto Giordano n° 0407**
6. Declared performance/s:

Essential characteristics	Performance
<b>Reaction to fire</b>	<b>Class A1</b>
<b>Adhesion</b>	<b>≥ 0,9 N/mm<sup>2</sup> FP:B</b>
<b>Water absorption</b>	<b>W<sub>c</sub> 2</b>
<b>Water vapour diffusion coeff.</b>	<b>μ 16</b>
<b>Thermal conductivity</b>	<b>0,45 W/mK (tab. Value)</b>
<b>Durability</b>	<b>NPD</b>
<b>Release of dangerous substances</b>	<b>See SDS</b>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia (legal representative)**

At Castellón, on 10/06/2022