



## **DECLARATION OF PERFORMANCE No. 0382**

1. Unique identification code of the product-type: RESYBRID 50 FC

2. Intended use/es: Sealant for internal application, non-structural use: facade joints.#

3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France

4. System/s of AVCP:

System 3 and System 3 for reaction to fire

5. Harmonised standard: EN 15651-1:2012

Notified body/ies: GINGER CEBTP, No. 0074

####Laboratoire National de metrologie et d'Essais, No. 0071

**6.** Declared performance/s:

EN15651-1 F-INT

**Pretreatment: Method A** 

Substrate: aluminium; without primer

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow Loss of volume Adhesion-cohesion properties until failure at 23°C Durability	≤ 5 mm ≤ 45% ≥ 25% Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 05/02/2018