

kerakoll

DECLARATION OF PERFORMANCE No 0021

1. Unique identification code of the product-type: **ELASTIK ECO**

2. Intended use/es:

Improved dispersion adhesive for all internal and external tiling.

3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia

4. System/s of AVCP:

System 3

System 3 for reaction to fire

5. Harmonised standard: EN 12004:2007 + A1:2012

Notified body/ies: Modena Centro Prove No. 1599

Istituto Giordano No. 0407

6. Declared performance/s:

| Essential characteristics | Performance |
|--|-------------------------------------|
| Reaction to fire | Class A2-s1,d0/A2 _{fl} -s1 |
| Bond strength as: | |
| initial shear adhesion strength | ≥ 1,0 N/mm² |
| Durability for: | |
| shear adhesion strength after heat ageing | ≥ 1,0 N/mm² |
| shear adhesion strength at elevated temperatures | ≥ 1,0 N/mm² |
| shear adhesion strength after water immersion | ≥ 0,5 N/mm² |
| Release of dangerous substances | See SDS |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)** At Sassuolo, on 29/04/2019

Myledei

kerakoll.com