

Roller Clean

Eco-friendly cleaner for tools used to apply Aqua-Pur water-based varnishes and water-based varnishes in general.

Roller Clean guarantees easy cleaning and conservation over time of rollers, brushes and tools for varnishes and water-based products.



SLC
TECHNOLOGY



Rating 3

1. Ready-to-use
2. Effectively removes residues
3. Improves durability and coverage of rollers and brushes

- × VOC Low Emission
- ✓ Water Based
- × Solvent ≤ 15 g/kg
- ✓ Low Ecological Impact
- ✓ Health Care

Areas of application

→ Use

To clean residual traces of Aqua-Pur water-based varnishes and water-based varnishes in general from tools.

Do not use for diluting water-based paints, primer and waterproofing products, single and two-component reactive adhesives, adhesives dispersed in water solution.

Instructions for use

- If access to running water is available on site, drain the roller of excess varnish, rinse it using clean water in order to remove varnish residue, wring it out and soak it in a bucket with Roller Clean. Before next use, drain the roller from Roller Clean, rinse it using clean water and dry it.
- If access to water on site is not available, prepare two buckets with Roller Clean, drain the roller

of excess varnish, rinse it in the first bucket of Roller Clean removing varnish residue, wring it out and soak it in the second bucket with clean Roller Clean. Check within a few hours whether it is necessary to rinse the roller again and soak it in clean Roller Clean. Before next use, drain the roller from Roller Clean, rinse it using clean water and dry it.

Technical Data compliant with Kerakoll Quality Standard

Appearance	Transparent liquid
Pack	10 l drums
Shelf life	≈ 12 months from the date of production in original and intact packaging
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C to +35 °C

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate.

Warning

- Product for professional use
- abide by any standards and national regulations
- respect the dilution ratios suggested in this data sheets and in the data sheet mentioned above

- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in December 2022 (ref. GBR Data Report – 12.22); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.